

Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse Care oil OB 52812-88009

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG Warendorfer Strasse 21

59075 Hamm

Telephone no. +49 (0) 2381 963-00 Fax no. +49 (0) 2381 963-849 E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

2. Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Aquatic Chronic 4 H413

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008 For explanation of abbreviations see section 16.

H226

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Flam. Liq. 3

Hazard pictograms



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

Further supplemental information ***

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

Young persons under 18 years may not work with this product.

2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

3. Composition/information on ingredients ***

Hazardous ingredients (Regulation (EC) No. 1272/2008) ***

alkanes, C11-14-iso-

CAS No. 90622-58-5

Concentration >= 30 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304 Aquatic Chronic 4 H413 EUH066

Naphtha (petroleum), hydrotreated heavy

CAS No. 64742-48-9 EINECS no. 265-150-3

Registration no. 01-2119463258-33

Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336 EUH066

Naphtha (petroleum), hydrotreated heavy

CAS No. 64742-48-9 EINECS no. 265-150-3

Registration no. 01-2119486659-16

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304

EUH066



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

2-ethylhexanoic acid zirconium salt

CAS No. 22464-99-9 EINECS no. 245-018-1

Registration no. 01-2119979088-21

Concentration >= 0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)

Repr. 2 H361d

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

4. First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.



Version: 7 / DK Revision: 02.01.2019

Replaces Version: 6 / DK Print date: 21.02.19

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do no eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

7.3. Specific end use(s)

See exposure scenario, if available.

8. Exposure controls/personal protection ***

8.1. Control parameters

Other information

_

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

Naphtha (petroleum), hydrotreated heavy

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure
Route of exposure
Mode of action

Long-term
Dermal exposure
Systemic effects

Concentration 300 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Long-term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 1500 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long-term

Dermal exposure

Systemic effects

Concentration 300 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long-term
Route of exposure inhalative

Mode of action Systemic effects

Concentration 900 mg/m³



Version: 7 / DK Revision: 02.01.2019

Replaces Version: 6 / DK Print date: 21.02.19

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Oral exposure

Mode of action Systemic effects

Concentration 300 mg/kg/d

Naphtha (petroleum), hydrotreated heavy

Type of value Derived No Effect Level (DNEL)

Reference group Workers (industrial)

Duration of exposure
Route of exposure
Mode of action

Long-term
Dermal exposure
Systemic effects

Concentration 208 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Workers (industrial)

Duration of exposure Long-term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 871 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Oral exposure

Mode of action Systemic effects

Concentration 125 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long-term

Dermal exposure

Systemic effects

Concentration 125 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 900 mg/m³

8.2. Exposure controls

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

Respiratory protection not applicable; Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material Nitrile rubber

Material thickness >= 0,4 mm Breakthrough time >= 30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form liquid Colour black

Odour characteristic

Odour threshold

Remarks not determined

pH value

Remarks not determined

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value 159 to 217 °C

Flash point

Value 36 to 55 °C

Evaporation rate

Remarks not determined

Flammability (solid, gas)

not determined



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

Upper/lower flammability or explosive limits

Remarks not determined

Vapour density

Remarks not determined

Density

Value appr. 0,899 kg/l

Temperature 20 °C

Solubility in water

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient: n-octanol/water

Remarks not determined

Ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

Viscosity

Remarks not determined

Efflux time

Value 57 s

Temperature 20 °C

Method DIN EN ISO 2431 - 4 mm

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

9.2. Other information

Non-volatile content

Value 50,6 %

Method calculated value

Other information

This information is not available.

10. Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

Isolate from sources of heat, sparks and open flame.

Decomposition temperature

Remarks not determined

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NOx), dense black smoke, No decomposition if used as prescribed.

11. Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Acute inhalational toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Sensitization

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

Other information

No toxicological data are available.

12. Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

Naphtha (petroleum), hydrotreated heavy

Species Pimephales promelas (fathead minnow) LC50 2200 mg/l

Duration of exposure 96 h

Naphtha (petroleum), hydrotreated heavy

Species Pimephales promelas (fathead minnow)
NOEC 2,6 mg/l

Duration of exposure 14 d

Naphtha (petroleum), hydrotreated heavy

Species Oncorhynchus mykiss (rainbow trout)
LC50 16 mg/l
Duration of exposure 96 h

Daphnia toxicity (Components)

Naphtha (petroleum), hydrotreated heavy

Species Chaetogammarus marinus

EC50 2,6 mg/l

Duration of exposure 96 h

alkanes, C11-14-iso-

Species Daphnia magna (Water flea)

EC50 > 1000 mg/l

Duration of exposure 48 h

Naphtha (petroleum), hydrotreated heavy

Species Daphnia magna (Water flea)

EC50 4,5 mg/l

Duration of exposure 48 h

Naphtha (petroleum), hydrotreated heavy

Species Daphnia magna (Water flea)

NOEC 2,6 mg/l

Duration of exposure 21 d

Algae toxicity (Components)

Naphtha (petroleum), hydrotreated heavy

Species Pseudokirchneriella subcapitata (green algae) EC50 3,1 mg/l

Duration of exposure 72 h

Bacteria toxicity (Components)

linseed oil

Species Pseudomonas putida

EC10 67000 mg/l



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

alkanes, C11-14-iso-

evaluation Not readily biodegradable.

Naphtha (petroleum), hydrotreated heavy

Value 77.05 %

Duration of test 28 d evaluation Readily biodegradable.

Ready degradability (Components)

linseed oil

Value appr. 40 %

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient: n-octanol/water

Remarks not determined

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

12.6. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

13. Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic

solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing

dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

modified product

EWC waste code 080113 - sludges from paint or varnish containing organic

solvents or other dangerous substances

EWC waste code 080115 - aqueous sludges containing paint or varnish

containing organic solvents or other dangerous substances

Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those

falling under 080111

Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated

by dangerous substances

Completely emptied packagings can be given for recycling.

14. Transport information

Land transport ADR/RID

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3 Label 3

14.4. Packing group

Packing group III
Limited Quantity 5 I
Transport category 3
Tunnel restriction code D/E

Marine transport IMDG/GGVSee

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III

Air transport ICAO/IATA

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class

14.4. Packing group

Packing group III

15. Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance



Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

or mixture

VOC ***

VOC (EU) 49,4 % 444 g/l

MAL-Code

MAL-Code 2-1

MAL 641,02 m³/l

Other information

All components are contained in the TSCA inventory or exempted.

15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

16. Other information

Hazard statements listed in Chapter 3

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H413 May cause long lasting harmful effects to aquatic life.

CLP categories listed in Chapter 3

Aquatic Chronic 4 Hazardous to the aquatic environment, chronic, Category 4

Asp. Tox. 1 Aspiration hazard, Category 1
Flam. Liq. 3 Flammable liquid, Category 3
Repr. 2 Reproductive toxicity, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning theInternational Transport of Dangerous Goods by Rail)

IMDG - International Maritime Code for Dangerous Goods

IATA - International Air Transport Association

IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS - Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL - Lowest Observed Adverse Effect Level

LOEL - Lowest Observed Effect Level

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Economic Cooperation and Development

VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Hesse Care oil OB 52812-88009

Version: 7 / DK Revision: 02.01.2019
Replaces Version: 6 / DK Print date: 21.02.19

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.